



Total creepage [mm]	260
Air-distance [mm]	130
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	7,35	PARALLEL ELEM.	7		
Q_N [kvar]	300	GROUPS IN SERIES	2	CONNECTION	Y
C_N [μ F]	3x 17,7 (-5/+10%)	WEIGHT [kg]	45	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	13,0	DIMENSIONS:	
I_N [A]	23,6	STANDARD	IEC 60871-1/05	A [mm]	145
BIL [kV]	28/75	INT. FUSES	YES	B [mm]	640
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	C [mm]	840
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	D [mm]	100
DISCHARGE	75 V/600 s (3x 4,7 M Ω)			DRAWN:	Stehlík J.

DRAWING No.:	4J9702C	TYPE:	CPEFS 23-7,35/300/WF-M1/PS	CHECKED:	Prokopec M.
				DATE:	28.4.2015

	ZEZ SILKO s.r.o. Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 01 Žamberk Czech Republic	tel.: +420 465 673 111 fax.: +420 465 612 319 e-mail: zez@zez-silko.cz http:// www.zez-silko.cz
--	--	--	--