



Total creepage [mm]	260
Air-distance [mm]	130
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	8,6	PARALLEL ELEM.	8		
Q_N [kvar]	800	GROUPS IN SERIES	4	CONNECTION	D
C_N [µF]	3x 11,48 (-5/+10%)	WEIGHT [kg]	103	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	29,8	DIMENSIONS:	
I_N [A]	53,7	STANDARD	IEC 60871-1/05	A [mm]	200
BIL [kV]	28/75	INT. FUSES	YES	B [mm]	1170
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	C [mm]	1370
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	D [mm]	100
DISCHARGE	75 V/600 s (3x 2,35 MΩ)			DRAWN:	Stehlík J.
DRAWING No.:	4K1524A	TYPE:	CPEFS 23-8,6/800/WF/D-M1	CHECKED:	Prokopec M.
				DATE:	10.4.2015



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 01 Žamberk
Czech Republic

tel.: +420 465 673 111
fax.: +420 465 612 319
e-mail: zez@zez-silko.cz
http:// www.zez-silko.cz