



Total creepage [mm]	260
Air-distance [mm]	130
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	7,2	PARALLEL ELEM.	12	CONNECTION	Y
Q_N [kvar]	600	GROUPS IN SERIES	2	CASE MATERIAL	Stainless steel
C_N [μ F]	3x 36,8 (-5/+10%)	WEIGHT [kg]	76	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	21,1	A [mm]	175
I_N [A]	48,1	STANDARD	IEC 60871-1/05	B [mm]	960
BIL [kV]	28/75	INT. FUSES	YES	C [mm]	1160
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES		
DISCHARGE	75 V/600 s (3x 2,35 M Ω)				

DRAWING No.:	4J6107Bb	TYPE:	CPEFS 23-7,2/600/WF-M1	DRAWN:	Stehlík J.
				CHECKED:	Prokopec M.
				DATE:	9.4.2015

	ZEZ SILKO s.r.o. Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 01 Žamberk Czech Republic	tel.: +420 465 673 111 fax.: +420 465 612 319 e-mail: zez@zez-silko.cz http:// www.zez-silko.cz
--	--	--	--