



Total creepage [mm]	317
Air-distance [mm]	165
Dry-flashover [kV]	85
Wet-flashover [kV]	50
Drywithstand [kV]	50
Wetwithstand [kV]	38
Impulse voltage [kV]	95

$U_N$ [kV]	11	PARALLEL ELEM.	7
$Q_N$ [kvar]	500	GROUPS IN SERIES	3
$C_N$ [ $\mu$ F]	3x 13,2 (-5/+10%)	WEIGHT [kg]	67
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	17,5
$I_N$ [A]	26,2	STANDARD	IEC 60871-1/05
BIL [kV]	38/95	INT. FUSES	YES
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (3x 8 M $\Omega$ )		

CONNECTION	Y
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	175
B [mm]	810
C [mm]	1082
D [mm]	100

DRAWING No.:	4J6229Aa	TYPE:	CPEFS 23-11/500/WF-C3
--------------	----------	-------	-----------------------

DRAWN:	Stehlík J.
CHECKED:	Prokopec M.
DATE:	2.6.2015



**ZEZE SILKO s.r.o.**  
**Žamberk**  
**CZECH REPUBLIC**

ZEZE SILKO s.r.o.  
 Pod černým lesem 683  
 564 01 Žamberk  
 Czech Republic

tel.: +420 465 673 111  
 fax.: +420 465 612 319  
 e-mail: [zez@zez-silko.cz](mailto:zez@zez-silko.cz)  
 http:// [www.zez-silko.cz](http://www.zez-silko.cz)