



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

$U_N$ [kV]	6,3	PARALLEL ELEM.	13
$Q_N$ [kvar]	550	GROUPS IN SERIES	2
$C_N$ [µF]	3x 44,1 (-5/+10%)	WEIGHT [kg]	72
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	19,8
$I_N$ [A]	50,4	STANDARD	IEC 60871-1/05
BIL [kV]	20/60	INT. FUSES	YES
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (3x 2,2 MΩ)		

CONNECTION	Y
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	175
B [mm]	890
C [mm]	1110
D [mm]	100

DRAWING No.: 4J8592B	TYPE: CPEFS 23-6,3/550/WF-C2
----------------------	------------------------------

DRAWN:	Stehlík J.
CHECKED:	Prokopec M.
DATE:	25.5.2015

	<b>ZEZ SILKO s.r.o.</b> Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 01 Žamberk Czech Republic	tel.: +420 465 673 111 fax.: +420 465 612 319 e-mail: <a href="mailto:zez@zez-silko.cz">zez@zez-silko.cz</a> http:// <a href="http://www.zez-silko.cz">www.zez-silko.cz</a>
--	--	--	--