



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	8	PARALLEL ELEM.	11	U_N [kV]	8
Q_N [kvar]	500	GROUPS IN SERIES	2	CONNECTION	Y
C_N [µF]	3x 24,9 (-5/+10%)	WEIGHT [kg]	64	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	18,2	DIMENSIONS:	
I_N [A]	36,1	STANDARD	IEC 60871-1/05	A [mm]	175
BIL [kV]	20/60	INT. FUSES	YES	B [mm]	810
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	C [mm]	1030
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	D [mm]	100
DISCHARGE	75 V/600 s (3x 3,3 MΩ)			DRAWN: Stehlik J.	

DRAWING No.:	4J9567Aa	TYPE:	CPEFS 23-8/500/WF-C2	CHECKED:	Prokopec M.
				DATE:	21.5.2015

	ZEZ SILKO s.r.o. Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 01 Žamberk Czech Republic	tel.: +420 465 673 111 fax.: +420 465 612 319 e-mail: zez@zez-silko.cz http:// www.zez-silko.cz
--	--	--	--