



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,3	DISCHARGE	75V/600s (3x30M Ω)	CONNECTION	Y
Q_N [kvar]	50	WEIGHT [kg]	15	CASE MATERIAL	Stainless steel
C_N [μ F]	3x 4,01 (-5/+10%)	LIQUID CAP. [kg]	5,2	DIMENSIONS:	
f_N [Hz]	50	STANDARD	IEC 60871-1/05	A [mm]	145
I_N [A]	4,6	INT. FUSES	NO	B [mm]	170
BIL [kV]	20/60	SIDE BRACKETS	YES	C [mm]	390
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)			DRAWN:	Stehlík J.

DRAWING No.:	4J5891Af	TYPE:	CPEFS 23-6,3/50-C2	CHECKED:	Prokopec M.
				DATE:	13.4.2015



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 01 Žamberk
Czech Republic

tel.: +420 465 673 111
fax.: +420 465 612 319
e-mail: zez@zez-silko.cz
http:// www.zez-silko.cz